





Material Safety Data Shee	et
---------------------------	----

FM-200[®]

Version 2.1

Revision Date 07/11/2011

Ref. 130000036866

This SDS adheres to the standards and regulatory requirements of the United States and may not meet the regulatory requirements in other countries.

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name Tradename/Synonym	:	FM-200 [®] FE-227 2-Hydroperfluoropropane Propane, 1,1,1,2,3,3,3-Heptafluoro- HFC-227eaHP 2-Hydroheptafluoropropane Heptafluoropropane 2-H-heptafluoropropane 1,1,1,2,3,3,3-Heptafluoropropane R-227 R227 HFC-227ea
MSDS Number	:	13000036866
Product Use	:	Fire extinguishing agent
Manufacturer	:	DuPont 1007 Market Street Wilmington, DE 19898
Product Information Medical Emergency Transport Emergency	:	1-800-441-7515 (outside the U.S. 1-302-774-1000) 1-800-441-3637 (outside the U.S. 1-302-774-1139) CHEMTREC: 1-800-424-9300 (outside the U.S. 1-703-527-3887)

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Misuse or intentional inhalation abuse may lead to death without warning. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Rapid evaporation of the liquid may cause frostbite.

Potential Health Effects Skin

: Contact with liquid or refrigerated gas can cause cold burns and frostbite.



Material Safety Data Sheet **FM-200[®]** Version 2.1 Revision Date 07/11/2011 Ref. 13000036866 Eyes : Contact with liquid or refrigerated gas can cause cold burns and frostbite. Inhalation Misuse or intentional inhalation abuse may cause death without warning : symptoms, due to cardiac effects. Other symptoms potentially related to misuse or inhalation abuse are: Anaesthetic effects, Light-headedness, dizziness, confusion, incoordination, drowsiness, or unconsciousness, irregular heartbeat with a strange sensation in the chest, heart thumping, apprehension, feeling of fainting, dizziness or weakness. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Carcinogenicity None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, or OSHA, as a carcinogen. SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS Component CAS-No. Concentration 1,1,1,2,3,3,3-Heptafluoropropane 431-89-0 100 % SECTION 4. FIRST AID MEASURES Skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes. Take off all contaminated clothing immediately. Consult a physician. Wash contaminated clothing before re-use. Treat for frostbite if necessary by gently warming affected area. Eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Consult a physician if necessary. Inhalation : Remove from exposure, lie down. Move to fresh air. Keep patient warm and at rest. Artificial respiration and/or oxygen may be necessary. Consult a physician. 2/9

Material Safety	Data	Sheet
-----------------	------	-------



M-200 [®]	
ersion 2.1	
evision Date 07/11/2011	Ref. 130000036866
Induction	· la not considered a potential route of expedure
Ingestion	: Is not considered a potential route of exposure.
General advice	 Never give anything by mouth to an unconscious person. When symptoms persist or in all cases of doubt seek medical advice.
Notes to physician	: Because of possible disturbances of cardiac rhythm, catecholamine drugs,
	such as epinephrine, that may be used in situations of emergency life support should be used with special caution.
CTION 5. FIREFIGHTING ME	ASURES
Fire and Explosion Hazard	: The product is not flammable. Hazardous decomposition products : Hydrogen
	fluoride, Carbonyl fluoride
Suitable extinguishing media	
Suitable extinguishing media	: This material is a fire extinguishing agent.
CTION 6. ACCIDENTAL REL	: This material is a fire extinguishing agent.
CTION 6. ACCIDENTAL REL	: This material is a fire extinguishing agent. EASE MEASURES NG MEASURES and HANDLING (PERSONNEL) sections before proceeding with clear
CTION 6. ACCIDENTAL REL NOTE: Review FIRE FIGHTI up. Use appropriate PERSO	 This material is a fire extinguishing agent. EASE MEASURES NG MEASURES and HANDLING (PERSONNEL) sections before proceeding with clear NAL PROTECTIVE EQUIPMENT during clean-up. Evacuate personnel, thoroughly ventilate area, use self-contained breathing
CTION 6. ACCIDENTAL REL NOTE: Review FIRE FIGHTI up. Use appropriate PERSO Safeguards (Personnel)	 This material is a fire extinguishing agent. EASE MEASURES NG MEASURES and HANDLING (PERSONNEL) sections before proceeding with clear NAL PROTECTIVE EQUIPMENT during clean-up. Evacuate personnel, thoroughly ventilate area, use self-contained breathing apparatus. Keep upwind of leak - evacuate until gas has dispersed.
ECTION 6. ACCIDENTAL REL NOTE: Review FIRE FIGHTI up. Use appropriate PERSON Safeguards (Personnel) Spill Cleanup	 This material is a fire extinguishing agent. EASE MEASURES NG MEASURES and HANDLING (PERSONNEL) sections before proceeding with clear NAL PROTECTIVE EQUIPMENT during clean-up. Evacuate personnel, thoroughly ventilate area, use self-contained breathing apparatus. Keep upwind of leak - evacuate until gas has dispersed. Ventilate area using forced ventilation, especially low or enclosed places where heavy vapors might collect.
CTION 6. ACCIDENTAL REL NOTE: Review FIRE FIGHTI up. Use appropriate PERSON Safeguards (Personnel) Spill Cleanup	 This material is a fire extinguishing agent. EASE MEASURES NG MEASURES and HANDLING (PERSONNEL) sections before proceeding with clear NAL PROTECTIVE EQUIPMENT during clean-up. Evacuate personnel, thoroughly ventilate area, use self-contained breathing apparatus. Keep upwind of leak - evacuate until gas has dispersed. Ventilate area using forced ventilation, especially low or enclosed places where heavy vapors might collect. TORAGE
ECTION 6. ACCIDENTAL REL NOTE: Review FIRE FIGHTI up. Use appropriate PERSON Safeguards (Personnel) Spill Cleanup	 This material is a fire extinguishing agent. EASE MEASURES NG MEASURES and HANDLING (PERSONNEL) sections before proceeding with clear NAL PROTECTIVE EQUIPMENT during clean-up. Evacuate personnel, thoroughly ventilate area, use self-contained breathing apparatus. Keep upwind of leak - evacuate until gas has dispersed. Ventilate area using forced ventilation, especially low or enclosed places where heavy vapors might collect.
CTION 6. ACCIDENTAL REL NOTE: Review FIRE FIGHTI up. Use appropriate PERSON Safeguards (Personnel) Spill Cleanup	 This material is a fire extinguishing agent. EASE MEASURES NG MEASURES and HANDLING (PERSONNEL) sections before proceeding with clear NAL PROTECTIVE EQUIPMENT during clean-up. Evacuate personnel, thoroughly ventilate area, use self-contained breathing apparatus. Keep upwind of leak - evacuate until gas has dispersed. Ventilate area using forced ventilation, especially low or enclosed places where heavy vapors might collect. TORAGE Do not breathe gas. Avoid contact with skin, eyes and clothing. Provide sufficient air exchange and/or exhaust in work rooms. For personal protection see section 8. Wash hands thoroughly after handling. Wash clothing after use. Decomposition will occur when product comes in contact with open
CTION 6. ACCIDENTAL REL NOTE: Review FIRE FIGHTI up. Use appropriate PERSON Safeguards (Personnel) Spill Cleanup	 This material is a fire extinguishing agent. EASE MEASURES NG MEASURES and HANDLING (PERSONNEL) sections before proceeding with clear NAL PROTECTIVE EQUIPMENT during clean-up. Evacuate personnel, thoroughly ventilate area, use self-contained breathing apparatus. Keep upwind of leak - evacuate until gas has dispersed. Ventilate area using forced ventilation, especially low or enclosed places where heavy vapors might collect. TORAGE Substitution of the state of the state of the state of the state of the sufficient air exchange and/or exhaust in work rooms. For personal protection see section 8. Wash hands thoroughly after handling. Wash clothing after use. Decomposition will occur when product comes in contact with open flame or electrical heating elements.

FM-200 [®]	
1 111 200	



evision Date 07/11/2011	Ref. 130000036866
Storage	 Valve protection caps and valve cutlet threaded plugs must remain in place unless container is secured with valve outlet piped to use point. Do not drag, slide or roll cylinders. Never attempt to lift cylinder by its cap. Use a check valve or trap in the discharge line to prevent hazardous back flow into the cylinder. Cylinders should be stored upright and firmly secured to prevent falling or being knocked over. Separate full containers from empty containers. Keep at temperature not exceeding 52°C. Do not store near combustible materials. Keep container tightly closed in a dry and well-ventilated place. Store in original container. Protect from contamination. Avoid area where salt or other corrosive materials are present.
Storage temperature	: <52 °C (< 126 °F)
CTION 8. EXPOSURE CONTRO	DLS/PERSONAL PROTECTION
Engineering controls	: Use only with adequate ventilation. Keep container tightly closed.
Personal protective equipment	
Respiratory protection	: Wear NIOSH approved respiratory protection as appropriate.
	Wear NIOSH approved respiratory protection as appropriate.Additional protection: Impervious gloves
Respiratory protection	
Respiratory protection Hand protection	 Additional protection: Impervious gloves Safety glasses with side-shields Additionally wear a face shield where the possibility exists for face contact due to splashing, spraying or airborne
Respiratory protection Hand protection Eye protection	 Additional protection: Impervious gloves Safety glasses with side-shields Additionally wear a face shield where the possibility exists for face contact due to splashing, spraying or airborne contact with this material. Where there is potential for skin contact, have available and wear as

aterial Safety Data Shee	et OUPOND
M-200[®]	
ersion 2.1	
evision Date 07/11/2011	Ref. 130000036866
	ble Exposure Limit. Where governmentally imposed occupational exposure limits which in effect, such limits shall take precedence.
ECTION 9. PHYSICAL AND CH	IEMICAL PROPERTIES
Form Odor Melting point/range Boiling point Vapour Pressure Density	 Liquefied gas none -131 °C (-204 °F) -16.3 °C (2.7 °F) 4,547 hPa at 25 °C (77 °F) 1.388 g/cm3 at 25 °C (77 °F) (as liquid)
ECTION 10. STABILITY AND F	EACTIVITY : Stable at normal temperatures and storage conditions.
Incompatibility	: Alkali metals Alkaline earth metals, Powdered metals, Powdered metal salts
Hazardous decomposition products	: Hazardous decomposition products, Hydrogen fluoride, Carbonyl fluoride, Carbon monoxide, Carbon dioxide
Hazardous reactions	: Polymerization will not occur.
ECTION 11. TOXICOLOGICAL	INFORMATION
FM-200 [®] Inhalation 4 h LC50	: > 788698 ppm , rat
Inhalation	: dog Cardiac sensitization
Dermal	: not applicable
Oral	: not applicable
Skin irritation	: No skin irritation, Not tested on animals 5 / 9



FM-200 [®]				
Version 2.1				
Revision Date 07/11/2011		Ref. 130000036866		
		Not expected to cause skin irritation based on expert review of the properties of the substance.		
Eye irritation	:	No eye irritation, Not tested on animals Not expected to cause eye irritation based on expert review of the properties of the substance.		
Sensitisation	:	Does not cause skin sensitization., Not tested on animals Not expected to cause sensitization based on expert review of the properties of the substance.		
		Did not cause sensitization on laboratory animals. There are no reports of human respiratory sensitization.		
Repeated dose toxicity	:	Inhalation rat No toxicologically significant effects were found.		
Carcinogenicity	:	Overall weight of evidence indicates that the substance is not carcinogenic.		
Mutagenicity	:	Did not cause genetic damage in animals. Did not cause genetic damage in cultured mammalian cells. Did not cause genetic damage in cultured bacterial cells.		
Reproductive toxicity	:	Animal testing showed no reproductive toxicity. Information given is based on data obtained from similar substances.		
Teratogenicity	:	Animal testing showed no developmental toxicity.		
Further information	:	Cardiac sensitisation threshold limit : 730190 mg/m3		
SECTION 12. ECOLOGICAL INFORMAT	SECTION 12. ECOLOGICAL INFORMATION			
Aquatic Toxicity				
FM-200 [®] 96 h LC50	:	Danio rerio (zebra fish) > 200 mg/l Information given is based on data obtained from similar substances.		
96 h LC50	:	Oncorhynchus mykiss (rainbow trout) > 81.8 mg/l		
		6/9		



FM-200 [®]		
Version 2.1		
Revision Date 07/1	1/2011	Ref. 130000036866
		Information given is based on data obtained from similar substances.
72 h E	C50	 Pseudokirchneriella subcapitata > 114 mg/l Information given is based on data obtained from similar substances.
72 h E	C50	: Pseudokirchneriella subcapitata > 118 mg/l Information given is based on data obtained from similar substances.
48 h E	C50	: Daphnia magna (Water flea) > 200 mg/l Information given is based on data obtained from similar substances.
48 h E	C50	: Daphnia magna (Water flea) > 97.9 mg/l Information given is based on data obtained from similar substances.
Environmental	Fate	
FM-200 [®] Biodeg	radability aerobic	: 1 % OECD Test Guideline 301 Not readily biodegradable.
Biodeg	radability aerobic	: 5 % OECD Test Guideline 301 Not readily biodegradable.
SECTION 13. DISP Waste Disposal	pern	DNS be used after re-conditioning. Recover by distillation or remove to a nitted waste disposal facility. Comply with applicable Federal, re/Provincial and Local Regulations.
Environmental F	lazards : Emp	bty pressure vessels should be returned to the supplier.
SECTION 14. TRAN	SPORT INFORMATIO	 N
DOT	UN number	: 3296
IATA_C	Proper shipping nam Class Labelling No. UN number	ne : Heptafluoropropane : 2.2 : 2.2 : 3296
		7/9

Material Safety Data Sheet
FLA O OOR



FM-200®

Version 2.1

Revision Date 07/11/2011

Ref. 130000036866

: Heptafluoropropane

Proper shipping name

IMDG

Class: 2.2Labelling No.: 2.2UN number: 3296Proper shipping name: HeptafluoropropaneClass: 2.2Labelling No.: 2.2

SECTION 15. REGULATORY INFORMATION

SARA 313 Regulated Chemical(s)	: SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
California Prop. 65	: Chemicals known to the State of California to cause cancer, birth defects or any other harm: none known

SECTION 16. OTHER INFORMATION

		HMIS
Health Flammability Reactivity/Physical hazard PPE	: :	1 0 0 Personal Protection rating to be supplied by user depending on use conditions.

FM-200 is a registered trademark of E. I. du Pont de Nemours and Company Before use read DuPont's safety information. For further information contact the local DuPont office or DuPont's nominated distributors. [®] DuPont's registered trademark

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing,



FM-200®

Version 2.1

Revision Date 07/11/2011

Ref. 13000036866

storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Significant change from previous version is denoted with a double bar.





Copyright © 2021. All rights reserved. ReedFOX™ are trademarks or registered trademarks of ReedFOX Fire & Life Safety Indonesia or its affiliates.